



Integrated Marketing Group

Integrated Marketing Group 2300

Integrated Marketing Group style 2300 is a **specialized plain weave fiberglass fabric**, featuring a unique acrylic coating on both sides. The superbly efficient coating and fabric are **fire-resistant**, in addition to being **specifically designed for slag resistance, spark resistance, and resistant to incidental flame from cutting torches**. 2300 functions optimally in applications such as use in vertical welding curtains for spark containment, flash barriers and heat shields. It can also used for protective clothing applications such as aprons and gloves. Standard colors for the acrylic coating include yellow, blue and black. Specialty colors can be made with minimum quantity purchase.



Values

Weight	23.0 oz/sy & 779.8 g/sm) +/- 10%
Thickness	0.034 inches (.8636 mm) +/- 10%
Tensile Strength	Warp: 200 lbs./inch (35.7 kg/cm) (35.7 kg/cm) Fill: 200 lbs./inch (35.7 kg/cm) (35.7 kg/cm)
Tear Strength	Warp: 45 lbs. (20.5 kg) (20.4 kg) Fill: 35 lbs. (15.9 kg) (15.8 kg)
Burst Strength	340 psi (23.9 kg/scm)
Flame Resistance	Char Length: 1/8 inch max Afterglow: 1 sec. max. Flame out: 1 sec. max.
Temperature Resistance	-40°F - 300°F (-40°C - 148.9°C)

1740 W. Katella Ave. Suite A, Orange, CA 92867
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.