



Integrated Marketing Group

Integrated Marketing Group 84215RW

Integrated Marketing Group 84215RW is a **specialized plain weave fiberglass fabric**, carefully designed with your heating protection needs in mind. IMG 84215RW **withstands high temperatures while still maintaining its powerful fabric strength**. This industrious fabric comes pre-pasted with adhesive and needs only to be dipped in water to soften and reactivate adhesion. It meets Military Specification **MIL-C-20079H, Type I, Class 4**. IMG style 84215RW is a trusted fabric, made specifically as a lagging and jacketing cloth for use over insulated surfaces and for removable insulation pads.

Values

Weight	14.3 oz/sy (484.9 g/sm) +/- 10%
Thickness	0.028 inches (.711 mm) +/- 10%
Tensile Strength	Warp: 100 lbs./inch (15.9 kg/cm) Fill: 50 lbs. (22.7 kg)/inch
Tear Strength	Warp: 15 lbs. (24.9 kg) Fill: 15 lbs. (24.9 kg)
Mullen Burst	150 psi (10.5 kg/scm)
Flame Resistance	Char length: 1 inch max. Afterglow: 1 sec. max. Flame out: 1 sec. max.
Temperature Resistance	450°F max (232.2°C)

1740 W. Katella Ave. Suite A, Orange, CA 92867
Phone: 714-771-2401 Fax: 714-771-3925

This information is given in good faith and is believed to be accurate and correct.